

8 COMMERCIAL ROAD READING, BERKSHIRE, RG2 0QZ, UK T: +44 (0) 118 918 2400 F: +44 (0) 118 986 7331

www.solderpaste.co.uk

SOLDER PASTE

3720

Tin-Bismuth Solder Paste - Lead Free*

3720 is a tin / bismuth solder paste designed for applications requiring low temperature soldering.

PASTE DATA

Solder Alloy: 42Sn / 58Bi

Particle Size: -200 / +325 mesh

Viscosity:

(Brookfield RVTD, Helipath Stand, 5 rpm, TF spindle, 25.5 ± 0.5 °C)

600 ± 50 Pa.s

Solids: $87 \pm 1.0 \%$

Eutectic Temperatures: 138 °C


Reflow Temperature: Standard reflow profile

Flux: Rosin Mildly Activated

Flux Removal: Limonene (Bioact EC-7)

3720 Typical Reflow Profile

(PASSAAT CONVECTION)



ESL Europe 3720 0507-C

*Complies with RoHS

CAUTION: Proper industrial safety precautions should be exercised in using these products. Use with adequate ventilation. Avoid prolonged contact with skin or inhalation of any vapours emitted during use or heating of these compositions. The use of safety eye goggles, gloves or hand protection creams is recommended. Wash hands or skin thoroughly with soap and water after using these products. Do not eat or smoke in areas where these materials are used. Refer to appropriate MSDS sheet.

DISCLAIMER: The product information and recommendations contained herein are based on data obtained by tests we believe to be accurate, but the accuracy and completeness thereof is not guaranteed. No warranty is expressed or implied regarding the accuracy of these data, the results obtained from the use hereof, or that any such use will not infringe any patent. ElectroScience assumes no liability for any injury, loss, or damage, direct or consequential, arising out of its use by others. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular use, before using it. User assumes all risk and liability whatsoever in connection with his intended use. ElectroScience's only obligation shall be to replace such quantity of the product proved defective.